



Universal wall outlet sockets




DB 03



DB 05



DB 07



Type	DB 03 Individual socket	DB 05 Loop-through socket	DB 07 Loop-through socket
Frequency range	5-2400 MHz	5-2400 MHz	5-2400 MHz
Thru loss 5-862 MHz	-	2.5 dB	1.0 dB
Thru loss 862-2400 MHz	-	3.0 dB	1.0 dB
Side loss TV/FM 5-862 MHz	4.5/4.5 dB	10/12 dB	14/14 dB
Side loss TV/FM 862-2400 MHz	5.0/5.0 dB	10/11 dB	15/15 dB
Return loss 40-2150 MHz, IN	Cat B	Cat B	Cat B
Return loss 40-2150 MHz, TV	Cat C	Cat C	Cat C
Isolation 5-40 MHz	>20 dB 2)	≥35 dB 1)	≥40 dB 1)4)
Isolation 40-862 MHz	>20 dB 2)	≥42 dB 1)3)	≥44 dB 1)
Isolation 862-2400 MHz	>20 dB 2)	≥35 dB 1)	≥40 dB 1)
Screening factor	> 85 dB, Class A	> 85 dB, Class A	> 85 dB, Class A
Cable connection outer/inner conductor	7.5/0.8-1.3 mm	7.5/0.8-1.3 mm	7.5/0.8-1.3 mm
Packing unit	10 pieces, 2.45 dm ³	10 pieces, 2.45 dm ³	10 pieces, 2.45 dm ³
Shipping package	100 pieces, 30 dm ³ , 8.9 kg	100 pieces, 30 dm ³ , 8.9 kg	100 pieces, 30 dm ³ , 8.9 kg
	1) between two sockets 2) isolation in one socket 3) up from 470 MHz ≥ 36 dB 4) up from 10 MHz		

