



Wall outlet sockets special types

DB 17



DB 33



Type	DB 17 Individual socket	DB 33 Individual socket
Frequency range IN	5-862 MHz	47-2150 MHz
Frequency range TV	-	47-862 MHz
Frequency range SAT	-	950-2150 MHz
Side loss TV 5-862 MHz	< 2.5 dB	-
Side loss FM 5-140 MHz	7.2 dB	-
Side loss TV 47-862 MHz	-	≤1.5 dB/<4.0 dB
Side loss SAT 950-2150 MHz	-	≤2.5 dB/<1.5 dB
Isolation FM-TV 5-30/30-140 MHz	≥20 dB/30-45 dB	-
Isolation IN-SAT 47-862 MHz	-	≥20 dB
Isolation IN-TV 950-2150 MHz	-	≥20 dB
Isolation TV-SAT	-	≥20 dB
Return loss IN	Cat B*	Cat B
Return loss TV	Cat C*	-
Return loss FM	Cat D*	-
Return loss TV/SAT	-	Cat C
Screening factor	> 85 dB, Class A	> 85 dB, Class A
Cable connection outer-/inner conductor	< 7.5/0.8-1.3 mm	< 7.5/0.8-1.3 mm
Packing unit	10 pieces, 2.45 dm ³	10 pieces, 2.45 dm ³
Shipping package	100 pieces, 30 dm ³ , 8.9 kg	100 pieces, 30 dm ³ , 8.9 kg
	*30 MHz, DB 33 with max. 500 mA DC bypass	

