

FIBER LINE accessories optical nodes



LT 40 S

Optical transmitter module, 1310 nm FP laser

Wavelength	1310 ±40nm
Broadband RF input	10-300 MHz
Frequency range	depending on diplex filter 10-(30) 65 MHz
Nominal input level	75dBµV
Setting range OMI	3-10% @75 dBµV input
Optical output power	3 dBm
Pilot frequency	6.5 MHz
Optical connector	SC/APC, E2000 on request!

LT 41 S



Optical transmitter module, 1310 nm DFB laser

Wavelength	1310 ± 20 nm
Broadband RF input	10-300 MHz
Frequency range	depending on diplex filter 10-(30) 65 MHz
Nominal input level	75 dBµV
Setting range OMI	3-10% @75 dBµV input
Optical output power	3 dBm
Pilot frequency	6.5 MHz
Optical connector	SC/APC, E2000 on request!

LT 45 S 1430

Optical transmitter module, 1430 nm CWDM

Wavelength	1430 ±3 nm
Pilot frequency	5,8 MHz

LT 45 S 1450

Optical transmitter module, 1450 nm CWDM

Wavelength	1450 ±3 nm
Pilot frequency	6,0 MHz

LT 45 S 1470

Optical transmitter module, 1470 nm CWDM

Wavelength	1470 ±3 nm
Pilot frequency	6,2 MHz

LT 45 S 1490

Optical transmitter module, 1490 CWDM

Wavelength	1490 ±3 nm
Pilot frequency	6,4 MHz

